

USB-C USB-A Dock - Hybrid Universal USB 3.0 Docking Station for USB-C or USB-A Laptop - Dual Monitor 4K 60Hz HDMI/DisplayPort - 6x USB-A, GbE - USB 3.1 Gen 1 - Windows/Mac

N° de produit: DK30A2DHUUE

Transition from the legacy USB-A (USB 3.0) to the new USB-C with this universal laptop docking station for USB-C and USB-A laptops. The USB 3.2 Gen 2 (10Gbps) Type-C dock features dual HDMI and/or DisplayPort monitors, fast-charge, six USB Type-A downstream peripheral ports, and headset audio.

This is a dual 4K60Hz video docking station with support for both Ultra HD DisplayPort and/or HDMI monitors that lets you configure your video connections to best suit your needs.

Dual 4K DisplayPort | Up to 4096 x 2160p @ 60Hz

Dual 4K HDMI | Up to 4096 x 2160p @ 60Hz

Single 4K DisplayPort + Single 4K HDMI | Up to 4096 x 2160p @ 60Hz

Single 5K DisplayPort\* | Up to 5120 x 2880

\*Requires monitor support for 5K using two DP ports

This docking station is fully certified to meet top industry standards for DisplayLink (video connections) certification to guarantee the highest quality, performance, and compatibility.

For fast setup right out of the box, the two included host cables (USB-C and USB-A) connect to any laptop. The included dock stand lets you position the dock vertically to save space or lay flat on the desk.


Connect your devices with six downstream USB Type-A (USB 3.0 5 Gbps) ports, two positioned on the front, and four on the back. The dock provides a GbE port and a 3.5 mm 4-position headset audio jack.

StarTech.com conducts thorough compatibility and performance testing on all our products to ensure we are meeting or exceeding industry standards and providing high-quality products to IT Professionals. Our local StarTech.com Technical Advisors have broad product expertise and work directly with our StarTech.com Engineers to provide support for our customers both pre and post-sales.

DK30A2DHUUE is backed by a StarTech.com 3-year warranty and free lifetime technical support.

## Certifications, rapports et compatibilité

## Applications



## Spécifications techniques

- **LATEST MODEL:** This USB-C USB-A dock offers the same functionality as DK30A2DH, with added flexibility of horizontal or vertical orientation using the included stand to save space at your workstation
- **HYBRID DOCK:** Universal USB 3.0 docking station works w/ USB-C & USB-A laptops/computers, using 2-in-1 USB-C/USB-A 3.3ft (1m) host cable, 6-Port USB Type-A hub, Gigabit Ethernet & headset audio jack
- **FLEXIBLE DUAL MONITOR VIDEO:** This 4K 60Hz USB-C or USB-A docking station can connect 2 monitors: Dual DisplayPort or Dual HDMI or DP + HDMI displays for easy deployment of multiple different screens
- **6 DOWNSTREAM USB-A PORTS:** Hybrid USB C dock has a 6-port USB 3.1/3.2 Gen 1 (5Gbps) hub w/ extra USB-A ports to support devices such as keyboard, mouse, flash drive, external hard drive & printer
- **COMPATIBILITY:** USB-C port replicator is DisplayLink Certified for max. performance & compatible w/ Dell, HP, Lenovo & MacBook PCs; Windows, Chrome and macOS platforms, where mixed laptop Brands used

---

### Matériel

Politique de garantie	3 Years
Prise en charge 4K	Oui
Port(s) à charge rapide	Oui
Écrans pris en charge	2
Nombre de ports	8
Prise en charge audio	Oui
Interface	USB 3.2 Gen 2 - 10 Gbit/s
Type de bus	USB-C
ID du chipset	DL-6950

---

### Performance

Résolutions numériques max.	4K 60 Hz
MTBF	26 280 hrs



---

#### Connecteur(s)

Types de connecteur	USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps)
	RJ-45
	HDMI
	DisplayPort
	Audio 3,5 mm
Connecteurs hôte	USB 3.1 USB Type-B (9 pin, Gen 1, 5 Gbps)

---

#### Logiciel

Compatibilité système d'exploitation	Windows® 2000, XP, Vista, 7, 8, 8.1, 10, macOS 10.6 - 10.12, 10.14 - 10.15, 11.0, Ubuntu 14.04, 16.04, 19.04, Linux Kernel 4.2 - 5.2, Chrome OS™ v55+
--------------------------------------	---

---

#### Alimentation

Adaptateur d'alimentation inclus	Adaptateur secteur inclus
Tension d'entrée	110V-240V AC
Courant d'entrée	1.0A
Tension de sortie	20V DC
Courant de sortie	2A
Type de prise	N
Consommation électrique	40W

---

#### Conditions environnementales

Température de fonctionnement	0 to 50°C
Température de stockage	-20 to 70°C
Humidité	0 % à 95 % (sans condensation) à 25 °C

---

#### Caractéristiqu



es physiques

Couleur	Black & Gray
Type de boîtier	Aluminium et plastique
Longueur de câble	39.4 in [100 cm]
Longueur du produit	2.9 in [73 mm]
Largeur du produit	5.3 in [13.5 cm]
Hauteur du produit	7.4 in [18.7 cm]
Poids du produit	12.0 oz [340 g]

---

Informations  
d'emballage

Package Length	4.3 in [10.9 cm]
Package Width	8.3 in [21 cm]
Package Height	5.6 in [14.2 cm]
Poids brut	12.7 oz [360 g]

---

Contenu du  
paquet

Inclus dans le paquet	Station d'Accueil
	Câble USB-C vers USB-B
	Câble USB-A vers USB-B
	Universal Power Adapter (UK/EU)
	Dock Stand
	Guide de démarrage rapide

---

\* L'apparence et les spécifications du produit peuvent être modifiées sans préavis

